

## OILGAS TRANSMISSION B 85W-140

### High multi-grade gear mineral oils

OILGAS TRANSMISSION B 85W-140, API GL-5 - are multi-grade gear mineral oils for manual transmissions of passenger cars and commercial vehicles, mobile equipment with different gear types which include hypoid (driving axles, transfer cases, steering gears etc.), where API GL-5 (TM-5) oils are recommended). OILGAS TRANSMISSION B 85W-140, API GL-5 is manufactured using highly refined mineral oils blended with advanced additive package improving oil performance.

### Application

OILGAS TRANSMISSION B 85W-140, API GL-5 is recommended for spur, spiral bevel, and hypoid gearboxes of passenger cars, trucks and other vehicles, as well as transfer cases, where API GL-5 (TM-5) oils are recommended. OILGAS TRANSMISSION B 85W-140, API GL-5 is approved for drive axles of BelAZ dump trucks of 30-90 MT carrying capacity exploited in a mild warm climate. OILGAS TRANSMISSION B 85W-140, API GL-5 provides the stable performance of the heavy loaded gears under maximum loads and in wide temperature range, especially in the hot and sharply continental climate and high-altitude as well.

Meets requirements	
API GL-5 NH 524A	VOLVO 97310 ZF TE-ML 07A, 08

### Typical test data

### OILGAS TRANSMISSION B 85W-140

Property	Test methods	Value
Viscosity index	ASTM D2270	100
Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	ASTM D445	25,5
Kinematic viscosity at 40 °C, mm <sup>2</sup> /s	ASTM D445	388,3
Flash point, °C	ASTM D92	226
Pour Point, °C	ASTM D 97/ SR 13552	- 15