

OIL GAS ENGICRAFT STANDARD 20W-50

Mineral, high-quality, super-high-performance (SHPD) for gasoline and diesel engines of mixed vehicle fleets EURO I-V, without DPF.

High-quality, super-high-performance, mineral, multigrade engine oil for gasoline and diesel engines of mixed vehicle fleets designed to comply with strict exhaust gas emissions limits EURO I, II, III, IV and V, without Diesel Particulate Filter (DPF). It provides significant reduction of the particle emissions, resulting in maximum protection of the environment. Its advanced additive technology guarantees maximum drain intervals and long engine lifespan.

Application

OILGAS ENGICRAFT STANDARD 20W-50 is specifically formulated for use in diesel engines within the mining industry, including those equipped with turbocharging, in accordance with the equipment's operational guidelines. This product is ideally suited for machinery that has accumulated significant operating hours, especially when utilizing lower-quality diesel fuels.

| Meets requirements | |
|------------------------------------|--|
| ACEA E7 API CI-4/SL MB 228.3 | |

| Typical test data | OILGAS ENGICRAFT STANDARD 20W-50 | |
|---|----------------------------------|-------|
| Property | Test methods | Value |
| Viscosity index | ASTM D 7042/ SR ISO 2909 | 142 |
| Kinematic viscosity at 100 °C, mm ² /s | ASTM D 7042 | 16,5 |
| Kinematic viscosity at 40 °C, mm ² /s | ASTM D 7042 | 125,3 |
| Flash point, °C | ASTM D92 | 226 |
| Pour Point, °C | ASTM D 97/ SR 13552 | - 30 |
| TBN | ASTM D 2896 | 12 |