

OILGAS ENGICRAFT SUPERIOR GT LA 10W-40

Fully Synthetic, high-quality, super-high-performance (SHPD), extremely low-ash diesel engine oil for commercial vehicles EURO V&VI, with DPF

High-quality, super-high-performance, synthetic, extremely low-ash, multigrade engine oil for commercial vehicles designed to reduce greenhouse gas emissions. The innovative formulation was specially designed for diesel engines of commercial vehicles equipped Selective Catalytic Reductor (SCR) system and/ or Diesel Particulate Filter (DPF), according to emissions regulations EURO V & VI. Also usable in EURO I, II, III & IV engines. It provides significant reduction of the particle emissions, resulting in longer particulate filter lifespan and maximum protection of the environment. Its advanced additive technology guarantees maximum drain intervals, rapid lubrication and long engine lifespan.

Application

OILGAS ENGICRAFT SUPERIOR GT LA 10W-40 was specially developed for modern VOLVO trucks and can be used in other modern heavy-duty engines, in accordance with the instructions from the vehicle manual.

Meets requirements	
API CK-4/ SN ACEA E7/ E9 Cummins CES 20086 Detroit Diesel DFS 93K222 Deutz DQC III-18 LA	Ford M2C171-F1 IVECO 18-1804 Classe TLS E9 Mack EOS-4.5 Renault VI RLD-3 VOLVO VDS-4.5

Typical test data		OILGAS ENGICRAFT SUPERIOR GT LA 10W-40
Property	Test methods	Value
Viscosity index	ASTM D 7042/ SR ISO 2909	154
Kinematic viscosity at 100 °C, mm ² /s	ASTM D 7042	14,2
Kinematic viscosity at 40 °C, mm ² /s	ASTM D 7042	94,3
Flash point, °C	ASTM D92	252
Pour Point, °C	ASTM D 97/ SR 13552	- 38
TBN	ASTM D 2896	13