

OIL GAS ENGICRAFT STANDARD 10W-40

Semi-synthetic, high-quality, super-high-performance (SHPD) for gasoline and diesel engines of mixed vehicle fleets EURO I-V, without DPF

High-quality, super-high-performance, semi-synthetic, multigrade engine oil for gasoline and diesel engines of mixed vehicle fleets designed to comply with strict exhaust gas emissions limits EURO I, II, III, IV and V, without Diesel Particulate Filter (DPF). It provides significant reduction of the particle emissions, resulting in maximum protection of the environment. Its advanced additive technology guarantees maximum drain intervals and long engine lifespan.

Application

OILGAS ENGICRAFT STANDARD 10W-40 is suitable for use in a mixed vehicle fleets, passenger cars and commercial vehicles, gasoline and diesel engines, including turbocharged, in accordance with the instructions from the vehicle manual.

Meets requirements	
API CI-4/SL ACEA E7 Caterpillar ECF-1-a/ ECF-2 Cummins CES 20071/ 20072/ 20076/ 20077/ 20078 Deutz DQC III-10 Mack EO-N	MAN M 3275-1 MB 228.3 MTU Oil Category 2 Renault VI RLD-2 VOLVO VDS-3

Typical test data

OILGAS ENGICRAFT STANDARD 10W-40

Property	Test methods	Value
Viscosity index	ASTM D 7042/ SR ISO 2909	162
Kinematic viscosity at 100 °C, mm ² /s	ASTM D 7042	14,79
Kinematic viscosity at 40 °C, mm ² /s	ASTM D 7042	95,54
Flash point, °C	ASTM D92	226
Pour Point, °C	ASTM D 97/ SR 13552	- 35
TBN	ASTM D 2896	10,4